

# Carbozinc 11 Part A

## Resene Paints (Australia) Limited

Version No: 6.29.10.8

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: 21/07/2021

Print Date: 21/07/2021

S.GHS.AUS.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | Carbozinc 11 Part A  |
| Chemical Name                 | Not Applicable   |
| Synonyms                      | Not Available  |
| Proper shipping name          | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |
| Other means of identification | Not Available  |

#### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Part A of a two pack industrial coating |
|--------------------------|---|

#### Details of the supplier of the safety data sheet

| Registered company name | Resene Paints (Australia) Limited                         | Altex Coatings Ltd   |
|-------------------------|---|--|
| Address                 | 7 Production Avenue, Molendinar Queensland 4214 Australia | 91-111 Oropi Road Tauranga 3112 New Zealand                      |
| Telephone               | +61 7 55126600  | +64 7 541 1221   |
| Fax                     | +64 7 541 1310  | +64 7 541 1310   |
| Website                 | <a href="http://www.resene.com.au">www.resene.com.au</a>  | <a href="http://www.altexcoatings.com">www.altexcoatings.com</a> |
| Email                   | Not Available   | neil.debenham@carboline.co.nz                                    |

#### Emergency telephone number

| Association / Organisation        | AUSTRALIAN POISONS CENTRE | NZ POISONS (24hr 7 days) | CHEMWATCH EMERGENCY RESPONSE |
|-----------------------------------|---------------------------|--------------------------|------------------------------|
| Emergency telephone numbers       | 131126                    | 0800 764766              | +61 2 9186 1132              |
| Other emergency telephone numbers | Not Available             | Not Available            | +61 1800 951 288             |

Once connected and if the message is not in your preferred language then please dial 01

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

|                    |   |
|--------------------|---|
| Poisons Schedule   | Not Applicable  |
| Classification [1] | Flammable Liquid Category 3, Eye Irritation Category 2A, Specific target organ toxicity - single exposure Category 3 (narcotic effects), Acute Toxicity (Inhalation) Category 4, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Reproductive Toxicity Category 2, Specific target organ toxicity - repeated exposure Category 1, Carcinogenicity Category 2, Chronic Aquatic Hazard Category 4 |
| Legend:            | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI   |

#### Label elements

|                     |   |
|---------------------|---|
| Hazard pictogram(s) |  |
| Signal word         | Danger  |

#### Hazard statement(s)

|      |  |
|------|--|
| H226 | Flammable liquid and vapour.                         |
| H319 | Causes serious eye irritation.                       |
| H336 | May cause drowsiness or dizziness.                   |
| H332 | Harmful if inhaled.                                  |
| H335 | May cause respiratory irritation.                    |
| H361 | Suspected of damaging fertility or the unborn child. |

## Carbozinc 11 Part A

|      |   |
|------|---|
| H372 | Causes damage to organs through prolonged or repeated exposure. |
| H351 | Suspected of causing cancer.                                    |
| H413 | May cause long lasting harmful effects to aquatic life.         |

## Supplementary statement(s)

Not Applicable

## Precautionary statement(s) Prevention

|      |  |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P260 | Do not breathe mist/vapours/spray.   |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P280 | Wear protective gloves, protective clothing, eye protection and face protection.               |
| P240 | Ground and bond container and receiving equipment.   |
| P241 | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.              |
| P242 | Use non-sparking tools.  |
| P243 | Take action to prevent static discharges.  |
| P270 | Do not eat, drink or smoke when using this product.  |
| P273 | Avoid release to the environment.  |
| P264 | Wash all exposed external body areas thoroughly after handling.                                |

## Precautionary statement(s) Response

|                |  |
|----------------|--|
| P308+P313      | IF exposed or concerned: Get medical advice/ attention.  |
| P370+P378      | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P312           | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.  |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].                         |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |

## Precautionary statement(s) Storage

|           |  |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P405      | Store locked up.                             |

## Precautionary statement(s) Disposal

|      |  |
|------|--|
| P501 | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|------|--|

## SECTION 3 Composition / information on ingredients

## Substances

See section below for composition of Mixtures

## Mixtures

| CAS No   | %[weight] | Name                            |
|----------|-----------|---------------------------------|
| 64-17-5. | 10-20     | ethanol_denatured               |
| 67-63-0  | 10-20     | isopropanol                     |
| 111-76-2 | 1-10      | ethylene glycol monobutyl ether |

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; \* EU IOELVs available

## SECTION 4 First aid measures

## Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>  |

## Carbozinc 11 Part A

|                   |  |
|-------------------|--|
| <b>Inhalation</b> | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>  |
| <b>Ingestion</b>  | <ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul> |

### Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

Treat symptomatically.

## SECTION 5 Firefighting measures

### Extinguishing media

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>  |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Liquid and vapour are flammable.</li> <li>▶ Moderate fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Moderate explosion hazard when exposed to heat or flame.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include:<br/>carbon monoxide (CO)<br/>carbon dioxide (CO<sub>2</sub>)<br/>other pyrolysis products typical of burning organic material.</p> <p><b>WARNING:</b> Long standing in contact with air and light may result in the formation of potentially explosive peroxides.</p> |
| <b>HAZCHEM</b>               | *3Y  |

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>▶ Wipe up.</li> <li>▶ Collect residues in a flammable waste container.</li> </ul>  |
| <b>Major Spills</b> | <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> </ul> |

Continued...

## Carbozinc 11 Part A

- ▶ Water spray or fog may be used to disperse /absorb vapour.
- ▶ Contain spill with sand, earth or vermiculite.
- ▶ Use only spark-free shovels and explosion proof equipment.
- ▶ Collect recoverable product into labelled containers for recycling.
- ▶ Absorb remaining product with sand, earth or vermiculite.
- ▶ Collect solid residues and seal in labelled drums for disposal.
- ▶ Wash area and prevent runoff into drains.
- ▶ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

## Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of overexposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid generation of static electricity.</li> <li>▶ <b>DO NOT use plastic buckets.</b></li> <li>▶ Earth all lines and equipment.</li> <li>▶ Use spark-free tools when handling.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ Store away from incompatible materials in a cool, dry, well-ventilated area.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access.</li> <li>▶ Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances.</li> <li>▶ Use non-sparking ventilation systems, approved explosion proof equipment and intrinsically safe electrical systems.</li> <li>▶ Have appropriate extinguishing capability in storage area (e.g. portable fire extinguishers - dry chemical, foam or carbon dioxide) and flammable gas detectors.</li> <li>▶ Keep adsorbents for leaks and spills readily available.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>                                    |

## Conditions for safe storage, including any incompatibilities

|                                |  |
|--------------------------------|--|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Lined metal can, lined metal pail/ can.</li> <li>▶ Plastic pail.</li> <li>▶ Polyliner drum.</li> <li>▶ Packing as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> <p>For low viscosity materials</p> <ul style="list-style-type: none"> <li>▶ Drums and jerricans must be of the non-removable head type.</li> <li>▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> </ul> |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.</li> </ul>  |



X — Must not be stored together

0 — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

## SECTION 8 Exposure controls / personal protection

## Control parameters

## Occupational Exposure Limits (OEL)

Continued...

## Carbozinc 11 Part A

## INGREDIENT DATA


| Source                       | Ingredient                      | Material name     | TWA                               | STEL                             | Peak          | Notes         |
|------------------------------|---------------------------------|-------------------|-----------------------------------|----------------------------------|---------------|---------------|
| Australia Exposure Standards | ethanol, denatured              | Ethyl alcohol     | 1000 ppm / 1880 mg/m <sup>3</sup> | Not Available                    | Not Available | Not Available |
| Australia Exposure Standards | isopropanol                     | Isopropyl alcohol | 400 ppm / 983 mg/m <sup>3</sup>   | 1230 mg/m <sup>3</sup> / 500 ppm | Not Available | Not Available |
| Australia Exposure Standards | ethylene glycol monobutyl ether | 2-Butoxyethanol   | 20 ppm / 96.9 mg/m <sup>3</sup>   | 242 mg/m <sup>3</sup> / 50 ppm   | Not Available | Not Available |

## Emergency Limits

| Ingredient                      | TEEL-1        | TEEL-2        | TEEL-3      |
|---------------------------------|---------------|---------------|-------------|
| ethanol, denatured              | Not Available | Not Available | 15000* ppm  |
| isopropanol                     | 400 ppm       | 2000* ppm     | 12000** ppm |
| ethylene glycol monobutyl ether | 60 ppm        | 120 ppm       | 700 ppm     |

| Ingredient                      | Original IDLH | Revised IDLH  |
|---------------------------------|---------------|---------------|
| ethanol, denatured              | 3,300 ppm     | Not Available |
| isopropanol                     | 2,000 ppm     | Not Available |
| ethylene glycol monobutyl ether | 700 ppm       | Not Available |

## Exposure controls

| Appropriate engineering controls  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying 'escape' velocities which, in turn, determine the 'capture velocities' of fresh circulating air required to effectively remove the contaminant.</p> |                        |   |  |  |   |                                  |  |   |                                  |
|---|---|------------------------|---|--|--|---|----------------------------------|--|---|----------------------------------|
|   | <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> </tbody> </table>  | Type of Contaminant:   | Air Speed:  | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min.)                               | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)       | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.)                |                                  |
|   | Type of Contaminant:  | Air Speed:             |   |  |  |   |                                  |  |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min.)  |                        |   |  |  |   |                                  |  |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)   | 0.5-1 m/s (100-200 f/min.)  |                        |   |  |  |   |                                  |  |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)  |                        |   |  |  |   |                                  |  |   |                                  |
| <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Lower end of the range  | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents  | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity  | 3: Intermittent, low production. | 3: High production, heavy use  | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
| Lower end of the range  | Upper end of the range  |                        |   |  |  |   |                                  |  |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                        |   |  |  |   |                                  |  |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity  |                        |   |  |  |   |                                  |  |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                        |   |  |  |   |                                  |  |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only  |                        |   |  |  |   |                                  |  |   |                                  |
| Personal protection   |    |                        |   |  |  |   |                                  |  |   |                                  |
| Eye and face protection   | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |                        |   |  |  |   |                                  |  |   |                                  |

## Carbozinc 11 Part A

|                              |  |
|------------------------------|--|
| <b>Skin protection</b>       | See Hand protection below  |
| <b>Hands/feet protection</b> | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| <b>Body protection</b>       | See Other protection below   |
| <b>Other protection</b>      | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul>  |

## Recommended material(s)

## GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**'Forsberg Clothing Performance Index'.**

The effect(s) of the following substance(s) are taken into account in the **computer-**

**generated** selection:

Carbozinc 11 Part A

| Material          | CPI |
|-------------------|-----|
| BUTYL             | C   |
| BUTYL/NEOPRENE    | C   |
| NAT+NEOPR+NITRILE | C   |
| NATURAL RUBBER    | C   |
| NATURAL+NEOPRENE  | C   |
| NEOPRENE          | C   |
| NEOPRENE/NATURAL  | C   |
| NITRILE           | C   |
| NITRILE+PVC       | C   |
| PE/EVAL/PE        | C   |
| PVA               | C   |
| PVC               | C   |

## Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the 'Exposure Standard' (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | AX-AUS               | -                    | AX-PAPR-AUS / Class 1  |
| up to 50 x ES                      | -                    | AX-AUS / Class 1     | -                      |
| up to 100 x ES                     | -                    | AX-2                 | AX-PAPR-2 ^            |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is

Continued...

## Carbozinc 11 Part A

|                  |   |
|------------------|---|
| PVDC/PE/PVDC     | C |
| SARANEX-23       | C |
| SARANEX-23 2-PLY | C |
| TEFLON           | C |
| VITON            | C |
| VITON/NEOPRENE   | C |

not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as 'feel' or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

## SECTION 9 Physical and chemical properties

## Information on basic physical and chemical properties

|   |                                    |  |               |
|---|------------------------------------|--|---------------|
| <b>Appearance</b>                                   | Coloured with Characteristic Odour |  |               |
| <b>Physical state</b>                               | Liquid                             | <b>Relative density (Water = 1)</b>            | 1.06          |
| <b>Odour</b>  | Not Available                      | <b>Partition coefficient n-octanol / water</b> | Not Available |
| <b>Odour threshold</b>                              | Not Available                      | <b>Auto-ignition temperature (°C)</b>          | 350           |
| <b>pH (as supplied)</b>                             | Not Available                      | <b>Decomposition temperature</b>               | Not Available |
| <b>Melting point / freezing point (°C)</b>          | Not Available                      | <b>Viscosity (cSt)</b>                         | 155.66        |
| <b>Initial boiling point and boiling range (°C)</b> | 104                                | <b>Molecular weight (g/mol)</b>                | Not Available |
| <b>Flash point (°C)</b>                             | 26                                 | <b>Taste</b>                                   | Not Available |
| <b>Evaporation rate</b>                             | 1.7 BuAC = 1                       | <b>Explosive properties</b>                    | Not Available |
| <b>Flammability</b>                                 | Flammable.                         | <b>Oxidising properties</b>                    | Not Available |
| <b>Upper Explosive Limit (%)</b>                    | 12.8                               | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available |
| <b>Lower Explosive Limit (%)</b>                    | 2.1                                | <b>Volatile Component (%vol)</b>               | 41            |
| <b>Vapour pressure (kPa)</b>                        | 3.6                                | <b>Gas group</b>                               | Not Available |
| <b>Solubility in water</b>                          | Immiscible                         | <b>pH as a solution (%)</b>                    | Not Available |
| <b>Vapour density (Air = 1)</b>                     | 2.4                                | <b>VOC g/L</b>                                 | 390           |

## SECTION 10 Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 Toxicological information

## Information on toxicological effects

|                |   |
|----------------|---|
| <b>Inhaled</b> | Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. |
|----------------|---|

## Carbozinc 11 Part A

|                     |  |
|---------------------|--|
|                     | Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.<br>Animal testing shows that the most common signs of inhalation overdose is inco-ordination and drowsiness.   |
| <b>Ingestion</b>    | The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models).<br>Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.<br>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result.  |
| <b>Skin Contact</b> | The material may accentuate any pre-existing dermatitis condition<br>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.<br>There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.  |
| <b>Eye</b>          | There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.  |
| <b>Chronic</b>      | There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.<br>Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.<br>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.<br>Based on experiments and other information, there is ample evidence to presume that exposure to this material can cause genetic defects that can be inherited.<br>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.<br>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.<br>Based on experience with animal studies, exposure to the material may result in toxic effects to the development of the foetus, at levels which do not cause significant toxic effects to the mother.<br>Ingestion may result in intoxication and drunkenness. In chronic form this may result in alcoholism and liver damage. |

|                            |                 |                   |
|----------------------------|-----------------|-------------------|
| <b>Carbozinc 11 Part A</b> | <b>TOXICITY</b> | <b>IRRITATION</b> |
|                            | Not Available   | Not Available     |

|                           |  |  |
|---------------------------|--|--|
| <b>ethanol, denatured</b> | <b>TOXICITY</b>                                  | <b>IRRITATION</b>  |
|                           | Dermal (rabbit) LD50: 17100 mg/kg <sup>[1]</sup> | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
|                           | Inhalation(Mouse) LC50; 39 mg/l4h <sup>[2]</sup> | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
|                           | Oral(Rat) LD50; >7692 mg/kg <sup>[1]</sup>       |  |

|                    |  |                                   |
|--------------------|--|-----------------------------------|
| <b>isopropanol</b> | <b>TOXICITY</b>                                    | <b>IRRITATION</b>                 |
|                    | Dermal (rabbit) LD50: 12792 mg/kg <sup>[1]</sup>   | Eye (rabbit): 10 mg - moderate    |
|                    | Inhalation(Mouse) LC50; 27.2 mg/l4h <sup>[2]</sup> | Eye (rabbit): 100 mg - SEVERE     |
|                    | Oral(Mouse) LD50; 3600 mg/kg <sup>[2]</sup>        | Eye (rabbit): 100mg/24hr-moderate |
|                    |  | Skin (rabbit): 500 mg - mild      |

|  |  |  |
|--|--|--|
| <b>ethylene glycol monobutyl ether</b> | <b>TOXICITY</b>                                  | <b>IRRITATION</b>  |
|  | Dermal (rabbit) LD50: 667 mg/kg <sup>[1]</sup>   | Eye (rabbit): 100 mg SEVERE                                      |
|  | Inhalation(Rat) LC50; 2.21 mg/l4h <sup>[2]</sup> | Eye (rabbit): 100 mg/24h-moderate                                |
|  | Oral(Guinea) LD50; 1414 mg/kg <sup>[1]</sup>     | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
|  |  | Skin (rabbit): 500 mg, open; mild                                |
|  |  | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
|  |  | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. \* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✓ | <b>Carcinogenicity</b>          | ✓ |
| <b>Skin Irritation/Corrosion</b>         | ✗ | <b>Reproductivity</b>           | ✓ |
| <b>Serious Eye Damage/Irritation</b>     | ✓ | <b>STOT - Single Exposure</b>   | ✓ |
| <b>Respiratory or Skin sensitisation</b> | ✗ | <b>STOT - Repeated Exposure</b> | ✓ |
| <b>Mutagenicity</b>                      | ✗ | <b>Aspiration Hazard</b>        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification



## Carbozinc 11 Part A

## Toxicity

| Carbozinc 11 Part A | Endpoint | Test Duration (hr) | Species       | Value         | Source        |
|---------------------|----------|--------------------|---------------|---------------|---------------|
|                     |          | Not Available      | Not Available | Not Available | Not Available |

| ethanol, denatured | Endpoint  | Test Duration (hr) | Species                       | Value      | Source |
|--------------------|-----------|--------------------|-------------------------------|------------|--------|
|                    | EC50(ECx) | 96h                | Algae or other aquatic plants | <0.001mg/L | 4      |
|                    | EC50      | 72h                | Algae or other aquatic plants | 275mg/l    | 2      |
|                    | LC50      | 96h                | Fish                          | >100mg/l   | 2      |
|                    | EC50      | 48h                | Crustacea                     | >79mg/L    | 4      |
|                    | EC50      | 96h                | Algae or other aquatic plants | <0.001mg/L | 4      |

| isopropanol | Endpoint  | Test Duration (hr) | Species                       | Value     | Source |
|-------------|-----------|--------------------|-------------------------------|-----------|--------|
|             | EC50(ECx) | 24h                | Algae or other aquatic plants | 0.011mg/L | 4      |
|             | EC50      | 72h                | Algae or other aquatic plants | >1000mg/l | 1      |
|             | LC50      | 96h                | Fish                          | 4200mg/l  | 4      |
|             | EC50      | 48h                | Crustacea                     | 7550mg/l  | 4      |
|             | EC50      | 96h                | Algae or other aquatic plants | >1000mg/l | 1      |

| ethylene glycol monobutyl ether | Endpoint  | Test Duration (hr) | Species                       | Value    | Source |
|---------------------------------|-----------|--------------------|-------------------------------|----------|--------|
|                                 | LC50      | 96h                | Fish                          | 1250mg/l | 2      |
|                                 | EC50      | 72h                | Algae or other aquatic plants | 623mg/l  | 2      |
|                                 | EC50      | 48h                | Crustacea                     | 164mg/l  | 2      |
|                                 | EC10(ECx) | 48h                | Crustacea                     | 7.2mg/l  | 2      |
|                                 | EC50      | 96h                | Algae or other aquatic plants | 720mg/l  | 2      |

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

**DO NOT discharge into sewer or waterways.**

## Persistence and degradability

| Ingredient                      | Persistence: Water/Soil     | Persistence: Air            |
|---------------------------------|-----------------------------|-----------------------------|
| ethanol, denatured              | LOW (Half-life = 2.17 days) | LOW (Half-life = 5.08 days) |
| isopropanol                     | LOW (Half-life = 14 days)   | LOW (Half-life = 3 days)    |
| ethylene glycol monobutyl ether | LOW (Half-life = 56 days)   | LOW (Half-life = 1.37 days) |

## Bioaccumulative potential

| Ingredient                      | Bioaccumulation      |
|---------------------------------|----------------------|
| ethanol, denatured              | LOW (LogKOW = -0.31) |
| isopropanol                     | LOW (LogKOW = 0.05)  |
| ethylene glycol monobutyl ether | LOW (BCF = 2.51)     |

## Mobility in soil

| Ingredient                      | Mobility          |
|---------------------------------|-------------------|
| ethanol, denatured              | HIGH (KOC = 1)    |
| isopropanol                     | HIGH (KOC = 1.06) |
| ethylene glycol monobutyl ether | HIGH (KOC = 1)    |

## SECTION 13 Disposal considerations

## Waste treatment methods

|                              |   |
|------------------------------|---|
| Product / Packaging disposal | <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> </ul> |
|------------------------------|---|

Continued...

## Carbozinc 11 Part A

|  |   |
|--|---|
|  | <ul style="list-style-type: none"> <li>▸ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▸ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▸ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▸ Where in doubt contact the responsible authority.</li> <li>▸ Recycle wherever possible.</li> <li>▸ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▸ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▸ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|--|---|

## SECTION 14 Transport information

## Labels Required

|                  |   |
|------------------|---|
|                  |  |
| Marine Pollutant | NO  |
| HAZCHEM          | *3Y   |

## Land transport (ADG)

|                              |  |                |
|------------------------------|--|----------------|
| UN number                    | 1263   |                |
| UN proper shipping name      | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |                |
| Transport hazard class(es)   | Class  | 3              |
|                              | Subrisk  | Not Applicable |
| Packing group                | III  |                |
| Environmental hazard         | Not Applicable   |                |
| Special precautions for user | Special provisions   | 163 223 367    |
|                              | Limited quantity   | 5 L            |

## Air transport (ICAO-IATA / DGR)

|                              |   |                |
|------------------------------|---|----------------|
| UN number                    | 1263  |                |
| UN proper shipping name      | Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base); Paint related material (including paint thinning or reducing compounds) |                |
| Transport hazard class(es)   | ICAO/IATA Class   | 3              |
|                              | ICAO / IATA Subrisk   | Not Applicable |
|                              | ERG Code  | 3L             |
| Packing group                | III   |                |
| Environmental hazard         | Not Applicable  |                |
| Special precautions for user | Special provisions  | A3 A72 A192    |
|                              | Cargo Only Packing Instructions   | 366            |
|                              | Cargo Only Maximum Qty / Pack   | 220 L          |
|                              | Passenger and Cargo Packing Instructions  | 355            |
|                              | Passenger and Cargo Maximum Qty / Pack  | 60 L           |
|                              | Passenger and Cargo Limited Quantity Packing Instructions   | Y344           |
|                              | Passenger and Cargo Limited Maximum Qty / Pack  | 10 L           |

## Sea transport (IMDG-Code / GGVSee)

|                            |  |                |
|----------------------------|--|----------------|
| UN number                  | 1263   |                |
| UN proper shipping name    | PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) |                |
| Transport hazard class(es) | IMDG Class   | 3              |
|                            | IMDG Subrisk   | Not Applicable |
| Packing group              | III  |                |
| Environmental hazard       | Not Applicable   |                |

## Carbozinc 11 Part A

|                              |                    |                 |
|------------------------------|--------------------|-----------------|
| Special precautions for user | EMS Number         | F-E , S-E       |
|                              | Special provisions | 163 223 367 955 |
|                              | Limited Quantities | 5 L             |

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name                    | Group         |
|---------------------------------|---------------|
| ethanol, denatured              | Not Available |
| isopropanol                     | Not Available |
| ethylene glycol monobutyl ether | Not Available |

## Transport in bulk in accordance with the ICG Code

| Product name                    | Ship Type     |
|---------------------------------|---------------|
| ethanol, denatured              | Not Available |
| isopropanol                     | Not Available |
| ethylene glycol monobutyl ether | Not Available |

## SECTION 15 Regulatory information

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## ethanol, denatured is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

## isopropanol is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australian Inventory of Industrial Chemicals (AIIC)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

## ethylene glycol monobutyl ether is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6Australian Inventory of Industrial Chemicals (AIIC)  
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

## National Inventory Status

| National Inventory                              | Status   |
|---|--|
| Australia - AIIC / Australia Non-Industrial Use | Yes  |
| Canada - DSL                                    | Yes  |
| Canada - NDLS                                   | No (ethanol, denatured; isopropanol; ethylene glycol monobutyl ether)  |
| China - IECSC                                   | Yes  |
| Europe - EINEC / ELINCS / NLP                   | Yes  |
| Japan - ENCS                                    | Yes  |
| Korea - KECI                                    | Yes  |
| New Zealand - NZIoC                             | Yes  |
| Philippines - PICCS                             | Yes  |
| USA - TSCA                                      | Yes  |
| Taiwan - TCSI                                   | Yes  |
| Mexico - INSQ                                   | Yes  |
| Vietnam - NCI                                   | Yes  |
| Russia - FBEPH                                  | Yes  |
| <b>Legend:</b>                                  | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

## SECTION 16 Other information

|               |            |
|---------------|------------|
| Revision Date | 21/07/2021 |
| Initial Date  | 18/01/2018 |

## SDS Version Summary

| Version   | Date of Update | Sections Updated   |
|-----------|----------------|--|
| 5.29.10.8 | 21/07/2021     | Acute Health (eye), Acute Health (inhaled), Acute Health (skin), Acute Health (swallowed), Advice to Doctor, Chronic Health, Classification, Disposal, Engineering Control, Environmental, Exposure Standard, Fire Fighter (fire/explosion hazard), Fire Fighter (fire fighting), First Aid (eye), First Aid (inhaled), First Aid (skin), Handling Procedure, Ingredients, Personal Protection (other), Personal Protection (Respirator), Physical Properties, Spills (major), Storage (storage incompatibility), Storage (storage requirement), Storage (suitable container), Transport |

Continued...

**Carbozinc 11 Part A****Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
ES: Exposure Standard  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index  
AIIIC: Australian Inventory of Industrial Chemicals  
DSL: Domestic Substances List  
NDSL: Non-Domestic Substances List  
IECSC: Inventory of Existing Chemical Substance in China  
EINECS: European INventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
NLP: No-Longer Polymers  
ENCS: Existing and New Chemical Substances Inventory  
KECI: Korea Existing Chemicals Inventory  
NZIoC: New Zealand Inventory of Chemicals  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
TSCA: Toxic Substances Control Act  
TCSI: Taiwan Chemical Substance Inventory  
INSQ: Inventario Nacional de Sustancias Químicas  
NCI: National Chemical Inventory  
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.

# Zinc Filler

## Resene Paints (Australia) Limited

Chemwatch Hazard Alert Code: 4

Version No: 6.11

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 22/02/2023

Print Date: 22/02/2023

S.GHS.AUS.EN

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

|                               |   |
|-------------------------------|---|
| Product name                  | Zinc Filler   |
| Synonyms                      | Not Available   |
| Proper shipping name          | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains zinc powder) |
| Other means of identification | Not Available   |

#### Relevant identified uses of the substance or mixture and uses advised against

|                          |  |
|--------------------------|--|
| Relevant identified uses | Part of a multi-component industrial coating |
|--------------------------|--|

#### Details of the manufacturer or supplier of the safety data sheet

|                         |   |  |
|-------------------------|---|--|
| Registered company name | Resene Paints (Australia) Limited                         | Altex Coatings Ltd   |
| Address                 | 7 Production Avenue, Molendinar Queensland 4214 Australia | 91-111 Oropi Road Tauranga 3112 New Zealand                      |
| Telephone               | +61 7 55126600  | +64 7 541 1221   |
| Fax                     | +61 7 55126697  | +64 7 541 1310   |
| Website                 | <a href="http://www.resene.com.au">www.resene.com.au</a>  | <a href="http://www.altexcoatings.com">www.altexcoatings.com</a> |
| Email                   | Not Available   | neil.debenham@carboline.co.nz                                    |

#### Emergency telephone number

|                                   |                           |                          |                                     |
|-----------------------------------|---------------------------|--------------------------|-------------------------------------|
| Association / Organisation        | AUSTRALIAN POISONS CENTRE | NZ POISONS (24hr 7 days) | CHEMWATCH EMERGENCY RESPONSE (24/7) |
| Emergency telephone numbers       | 131126                    | 0800 764766              | +61 1800 951 288                    |
| Other emergency telephone numbers | Not Available             | Not Available            | +61 3 9573 3188                     |

Once connected and if the message is not in your preferred language then please dial 01

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

|                    |   |
|--------------------|---|
| Poisons Schedule   | Not Applicable  |
| Classification [1] | Hazardous to the Aquatic Environment Long-Term Hazard Category 1, Flammable Solids Category 1                                       |
| Legend:            | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

#### Label elements

|                     |   |
|---------------------|---|
| Hazard pictogram(s) | The hazard pictogram consists of two diamond-shaped symbols. The first is a red diamond with a black flame, representing 'Flammable solid' (F+). The second is a red diamond with a black tree and a dead tree, representing 'Environment' (N). |
| Signal word         | Danger  |

#### Hazard statement(s)

|      |   |
|------|---|
| H410 | Very toxic to aquatic life with long lasting effects. |
| H228 | Flammable solid.                                      |

#### Supplementary statement(s)

Not Applicable

#### Precautionary statement(s) Prevention

|      |  |
|------|--|
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
|------|--|

## Zinc Filler

|             |   |
|-------------|---|
| <b>P240</b> | Ground and bond container and receiving equipment.                                |
| <b>P241</b> | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. |
| <b>P273</b> | Avoid release to the environment.   |
| <b>P280</b> | Wear protective gloves and protective clothing.                                   |

### Precautionary statement(s) Response

|                  |   |
|------------------|---|
| <b>P370+P378</b> | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish. |
| <b>P391</b>      | Collect spillage.   |

### Precautionary statement(s) Storage

Not Applicable

### Precautionary statement(s) Disposal

|             |  |
|-------------|--|
| <b>P501</b> | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|-------------|--|

## SECTION 3 Composition / information on ingredients

### Substances

See section below for composition of Mixtures

### Mixtures

| CAS No         | %[weight]  | Name               |
|----------------|--|--------------------|
| 7440-66-6      | >95  | <u>zinc powder</u> |
| 1314-13-2      | <=5  | <u>zinc oxide</u>  |
| <b>Legend:</b> | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available |                    |

## SECTION 4 First aid measures

### Description of first aid measures

|                     |   |
|---------------------|---|
| <b>Eye Contact</b>  | <p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> <li>▶ <b>DO NOT attempt to remove particles attached to or embedded in eye .</b></li> <li>▶ Lay victim down, on stretcher if available and pad <b>BOTH</b> eyes, make sure dressing does not press on the injured eye by placing thick pads under dressing, above and below the eye.</li> <li>▶ Seek urgent medical assistance, or transport to hospital.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>   |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>   |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>   |

### Indication of any immediate medical attention and special treatment needed

- ▶ Absorption of zinc compounds occurs in the small intestine.
- ▶ The metal is heavily protein bound.
- ▶ Elimination results primarily from faecal excretion.
- ▶ The usual measures for decontamination (Ipecac Syrup, lavage, charcoal or cathartics) may be administered, although patients usually have sufficient vomiting not to require them.
- ▶ CaNa2EDTA has been used successfully to normalise zinc levels and is the agent of choice.

[Ellenhorn and Barceloux: Medical Toxicology]

## SECTION 5 Firefighting measures

### Extinguishing media

Metal dust fires need to be smothered with sand, inert dry powders.

**DO NOT USE WATER, CO2 or FOAM.**

- ▶ Use DRY sand, graphite powder, dry sodium chloride based extinguishers, G-1 or Met L-X to smother fire.
- ▶ Confining or smothering material is preferable to applying water as chemical reaction may produce flammable and explosive hydrogen gas.
- ▶ Chemical reaction with CO2 may produce flammable and explosive methane.
- ▶ If impossible to extinguish, withdraw, protect surroundings and allow fire to burn itself out.
- ▶ **DO NOT** use halogenated fire extinguishing agents.

### Special hazards arising from the substrate or mixture

|                             |   |
|-----------------------------|---|
| <b>Fire Incompatibility</b> | ▶ Reacts with acids producing flammable / explosive hydrogen (H2) gas |
|-----------------------------|---|

Continued...

## Zinc Filler

- Segregate from alcohol, water.

## Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▸ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▸ May be violently or explosively reactive.</li> <li>▸ Wear full protective clothing plus breathing apparatus.</li> <li>▸ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▸ Consider evacuation (or protect in place)</li> <li>▸ <b>DO NOT</b> use water on fires.</li> </ul> <p><b>CAUTION:</b> If only water available, use flooding quantities of water or withdraw personnel.</p> <ul style="list-style-type: none"> <li>▸ <b>DO NOT</b> allow water to enter containers.</li> <li>▸ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▸ Cool fire exposed containers with flooding quantities of water from a protected location until well after fire is out.</li> <li>▸ If safe to do so, remove undamaged containers from path of fire.</li> <li>▸ If fire gets out of control withdraw personnel and warn against entry.</li> <li>▸ Equipment should be thoroughly decontaminated after use.</li> <li>▸ Fight fire from a protected position or use unmanned hose holders or monitor nozzles.</li> <li>▸ Withdraw immediately in case of rising sound from venting safety devices or discolouration of tanks.</li> <li>▸ ALWAYS stay away from tank ends.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▸ Zinc dust clouds are potentially explosive.</li> <li>▸ Electric sparks may ignite the dust cloud even in atmospheres containing low oxygen (10%).</li> <li>▸ In air the dust may be ignited in contact with hot surfaces or flame where temperatures exceed 600 deg C.</li> </ul> <p>Combustion products include:<br/>metal oxides</p>  |
| <b>HAZCHEM</b>               | 2Z   |

## SECTION 6 Accidental release measures

## Personal precautions, protective equipment and emergency procedures

See section 8

## Environmental precautions

See section 12

## Methods and material for containment and cleaning up

|                     |   |
|---------------------|---|
| <b>Minor Spills</b> | <p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none"> <li>▸ Material from spill may be contaminated with water resulting in generation of gas which subsequently may pressure closed containers.</li> <li>▸ Hold spill material in vented containers only and plan for prompt disposal</li> <li>▸ Eliminate all ignition sources.</li> <li>▸ Cover with <b>DRY</b> earth, sand or other non-combustible material.</li> <li>▸ Then cover with plastic sheet to minimise spreading and to prevent exposure to rain or other sources of water.</li> <li>▸ Use clean, non-sparking tools to collect absorbed material and place into loosely-covered metal or plastic containers ready for disposal.</li> <li>▸ Wear gloves and safety glasses as appropriate.</li> </ul>  |
| <b>Major Spills</b> | <p>Environmental hazard - contain spillage.</p> <ul style="list-style-type: none"> <li>· Do not use compressed air to remove metal dusts from floors, beams or equipment</li> <li>· Vacuum cleaners, of flame-proof design, should be used to minimise dust accumulation.</li> <li>· Use non-sparking handling equipment, tools and natural bristle brushes.</li> <li>· Provide grounding and bonding where necessary to prevent accumulation of static charges during metal dust handling and transfer operations</li> <li>· Cover and reseal partially empty containers.</li> <li>· Do not allow chips, fines or dusts to contact water, particularly in enclosed areas. <ul style="list-style-type: none"> <li>▸ Clear area of personnel and move upwind.</li> <li>▸ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▸ Eliminate all ignition sources (no smoking, flares, sparks or flames)</li> <li>▸ Stop leak if safe to do so; prevent entry into waterways, drains or confined spaces.</li> <li>▸ May be violently or explosively reactive.</li> <li>▸ <b>DO NOT walk through spilled material.</b></li> <li>▸ Wear full protective clothing plus breathing apparatus.</li> <li>▸ <b>DO NOT touch damaged containers or spilled material unless wearing appropriate protective clothing.</b></li> <li>▸ Water spray may be used to knock down vapours or divert vapour clouds; <b>DO NOT allow water to enter container or come into contact with the material.</b></li> <li>▸ Cover with <b>DRY</b> earth, sand, vermiculite or other non-combustible material.</li> <li>▸ Then cover with plastic sheet to minimise spreading and to prevent exposure to rain or other sources of water.</li> <li>▸ Use clean, non-sparking tools to collect absorbed material and place into loosely-covered metal or plastic containers ready for disposal.</li> <li>▸ Alternately, the spill may be contained using <b>DRY</b> earth, sand, or vermiculite and then covered with a high boiling point mineral oil.</li> <li>▸ Recover the liquid using non-sparking appliances and place in labelled, sealable container.</li> <li>▸ Wash spill area with detergent and water and dike for later disposal.</li> <li>▸ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>▸ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> </li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

## Precautions for safe handling

|                      |   |
|----------------------|---|
| <b>Safe handling</b> | <ul style="list-style-type: none"> <li>▸ Avoid all personal contact, including inhalation.</li> <li>▸ Wear protective clothing when risk of overexposure occurs.</li> <li>▸ Use in a well-ventilated area.</li> </ul> |
|----------------------|---|

Continued...

## Zinc Filler

|                          |  |
|--------------------------|--|
|                          | <ul style="list-style-type: none"> <li>▶ Avoid contact with moisture.</li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately and before re-use</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>   |
| <b>Other information</b> | <p><b>KEEP DRY!</b> Packages must be protected from water ingress.</p> <p><b>FOR MINOR QUANTITIES:</b></p> <ul style="list-style-type: none"> <li>▶ Store in an indoor fireproof cabinet or in a room of noncombustible construction and provide adequate portable fire-extinguishers in or near the storage area.</li> </ul> <p><b>FOR PACKAGE STORAGE:</b></p> <ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store away from incompatible materials in a cool, dry well ventilated area.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Protect containers from exposure to weather and from direct sunlight unless: (a) the packages are of metal or plastic construction; (b) the packages are securely closed are not opened for any purpose while in the area where they are stored; (c) adequate precautions are taken to ensure that rain water, which might become contaminated by the dangerous goods, is collected and disposed of safely.</li> <li>▶ Ensure proper stock-control measures are maintained to prevent prolonged storage of dangerous goods.</li> <li>▶ Automatic fire-sprinklers <b>MUST NOT</b> be installed in room or space.</li> <li>▶ The room or space must be located at least five metres from the boundaries of the premises and from other buildings unless separated by a wall with a fire resistance of at least four hours.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul> |

**Conditions for safe storage, including any incompatibilities**

|                                |  |
|--------------------------------|--|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ <b>CARE:</b> Packing of high density product in light weight metal or plastic packages may result in container collapse with product release</li> <li>▶ Heavy gauge metal packages / Heavy gauge metal drums</li> <li>▶ Storage containers must be hermetically sealed; the product must be stored under an inert, dry gas.</li> </ul> <p>For low viscosity materials and solids:<br/>Drums and jerricans must be of the non-removable head type.<br/>Where a can is to be used as an inner package, the can must have a screwed enclosure.</p>   |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Many metals may incandesce, react violently, ignite or react explosively upon addition of concentrated nitric acid.</li> <li>▶ Reacts slowly with water.</li> <li>▶ <b>CAUTION contamination with moisture will liberate explosive hydrogen gas, causing pressure build up in sealed containers.</b></li> <li>▶ Reacts violently with caustic soda, other alkalies - generating heat, highly flammable hydrogen gas.</li> <li>▶ If alkali is dry, heat generated may ignite hydrogen - if alkali is in solution may cause violent foaming</li> <li>▶ Segregate from alcohol, water.</li> </ul> <p>Metals exhibit varying degrees of activity. Reaction is reduced in the massive form (sheet, rod, or drop), compared with finely divided forms. The less active metals will not burn in air but:</p> <ul style="list-style-type: none"> <li>▶ can react exothermically with oxidising acids to form noxious gases.</li> <li>▶ catalyse polymerisation and other reactions, particularly when finely divided</li> <li>▶ react with halogenated hydrocarbons (for example, copper dissolves when heated in carbon tetrachloride), sometimes forming explosive compounds.</li> </ul> <ul style="list-style-type: none"> <li>▶ Finely divided metal powders develop pyrophoricity when a critical specific surface area is exceeded; this is ascribed to high heat of oxide formation on exposure to air.</li> <li>▶ Safe handling is possible in relatively low concentrations of oxygen in an inert gas.</li> <li>▶ Several pyrophoric metals, stored in glass bottles have ignited when the container is broken on impact. Storage of these materials moist and in metal containers is recommended.</li> <li>▶ The reaction residues from various metal syntheses (involving vacuum evaporation and co-deposition with a ligand) are often pyrophoric. Factors influencing the pyrophoricity of metals are particle size, presence of moisture, nature of the surface of the particle, heat of formation of the oxide, or nitride, mass, hydrogen content, stress, purity and presence of oxide, among others.</li> <li>▶ Many metals in elemental form react exothermically with compounds having active hydrogen atoms (such as acids and water) to form flammable hydrogen gas and caustic products.</li> <li>▶ Elemental metals may react with azo/diazo compounds to form explosive products.</li> <li>▶ Some elemental metals form explosive products with halogenated hydrocarbons.</li> </ul> |



X — Must not be stored together

0 — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

**SECTION 8 Exposure controls / personal protection****Control parameters****Occupational Exposure Limits (OEL)**

Continued...



## Zinc Filler

## INGREDIENT DATA

| Source                       | Ingredient | Material name     | TWA                  | STEL                 | Peak          | Notes  |
|------------------------------|------------|-------------------|----------------------|----------------------|---------------|--|
| Australia Exposure Standards | zinc oxide | Zinc oxide (fume) | 5 mg/m <sup>3</sup>  | 10 mg/m <sup>3</sup> | Not Available | Not Available  |
| Australia Exposure Standards | zinc oxide | Zinc oxide (dust) | 10 mg/m <sup>3</sup> | Not Available        | Not Available | (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica. |

## Emergency Limits

| Ingredient  | TEEL-1               | TEEL-2               | TEEL-3                  |
|-------------|----------------------|----------------------|-------------------------|
| zinc powder | 6 mg/m <sup>3</sup>  | 21 mg/m <sup>3</sup> | 120 mg/m <sup>3</sup>   |
| zinc oxide  | 10 mg/m <sup>3</sup> | 15 mg/m <sup>3</sup> | 2,500 mg/m <sup>3</sup> |


| Ingredient  | Original IDLH         | Revised IDLH  |
|-------------|-----------------------|---------------|
| zinc powder | Not Available         | Not Available |
| zinc oxide  | 500 mg/m <sup>3</sup> | Not Available |

## Occupational Exposure Banding

| Ingredient  | Occupational Exposure Band Rating | Occupational Exposure Band Limit |
|-------------|-----------------------------------|----------------------------------|
| zinc powder | E                                 | ≤ 0.01 mg/m <sup>3</sup>         |

**Notes:** Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

## Exposure controls

|  |   |
|--|---|
| <b>Appropriate engineering controls</b>                                      | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard 'physically' away from the worker and ventilation that strategically 'adds' and 'removes' air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> <li>▶ Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area.</li> <li>▶ Work should be undertaken in an isolated system such as a 'glove-box'. Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system.</li> <li>▶ Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within.</li> <li>▶ Open-vessel systems are prohibited.</li> <li>▶ Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation.</li> <li>▶ Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system.</li> <li>▶ For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> <li>▶ Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas).</li> <li>▶ Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air.</li> <li>▶ Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 0.76 m/sec with a minimum of 0.64 m/sec. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed.</li> </ul> |
| <b>Individual protection measures, such as personal protective equipment</b> |    |
| <b>Eye and face protection</b>   | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |
| <b>Skin protection</b>   | See Hand protection below   |
| <b>Hands/feet protection</b>   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p>  |

## Zinc Filler

|                         |   |
|-------------------------|---|
|                         | <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <ul style="list-style-type: none"> <li>▸ Protective gloves eg. Leather gloves or gloves with Leather facing</li> </ul> |
| <b>Body protection</b>  | See Other protection below  |
| <b>Other protection</b> | <ul style="list-style-type: none"> <li>▸ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]</li> <li>▸ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent]</li> <li>▸ Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.</li> <li>▸ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.</li> <li>▸ Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.</li> <li>▸ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▸ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▸ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul>  |

## Respiratory protection

Type -P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | P1<br>Air-line*      | -<br>-               | PAPR-P1<br>-           |
| up to 50 x ES                      | Air-line**           | P2                   | PAPR-P2                |
| up to 100 x ES                     | -                    | P3                   | -                      |
|                                    |                      | Air-line*            | -                      |
| 100+ x ES                          | -                    | Air-line**           | PAPR-P3                |

\* - Negative pressure demand \*\* - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Continued...

## Zinc Filler

Where significant concentrations of the material are likely to enter the breathing zone, a Class P3 respirator may be required.

Class P3 particulate filters are used for protection against highly toxic or highly irritant particulates.

Filtration rate: Filters at least 99.95% of airborne particles

Suitable for:

- Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
- Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.
- Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS
- Highly toxic particles e.g. Organophosphate Insecticides, Radionuclides, Asbestos

Note: P3 Rating can only be achieved when used with a Full Face Respirator or Powered Air-Purifying Respirator (PAPR). If used with any other respirator, it will only provide filtration protection up to a P2 rating.

### SECTION 9 Physical and chemical properties

#### Information on basic physical and chemical properties

|   |                        |  |                |
|---|------------------------|--|----------------|
| <b>Appearance</b>                                   | grey powder            |  |                |
| <b>Physical state</b>                               | Divided Solid <br>Dust | <b>Relative density (Water = 1)</b>            | 7.6            |
| <b>Odour</b>  | Not Available          | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available          | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Available          | <b>Decomposition temperature (°C)</b>          | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available          | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available          | <b>Molecular weight (g/mol)</b>                | Not Available  |
| <b>Flash point (°C)</b>                             | Not Applicable         | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available BuAC = 1 | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Not Applicable         | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available          | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Applicable |
| <b>Lower Explosive Limit (%)</b>                    | Not Available          | <b>Volatile Component (%vol)</b>               | Negligible     |
| <b>Vapour pressure (kPa)</b>                        | Not Available          | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water</b>                          | Immiscible             | <b>pH as a solution (1%)</b>                   | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | Not Available          | <b>VOC g/L</b>                                 | 0.00           |

### SECTION 10 Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>· Unstable in the presence of incompatible materials</li> <li>▶ May heat spontaneously</li> <li>▶ Identify and remove sources of ignition and heating.</li> <li>▶ Incompatible material, especially oxidisers, and/or other sources of oxygen may produce unstable product(s).</li> <li>▶ Avoid sources of water contamination (e.g. rain water, moisture, high humidity).</li> <li>▶ Avoid contact with oxygenated solvents/ reagents such as alcohols.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

### SECTION 11 Toxicological information

#### Information on toxicological effects

|                |  |
|----------------|--|
| <b>Inhaled</b> | <p>The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.</p> <p>Persons with impaired respiratory function, airway diseases and conditions such as emphysema or chronic bronchitis, may incur further disability if excessive concentrations of particulate are inhaled.</p> <p>If prior damage to the circulatory or nervous systems has occurred or if kidney damage has been sustained, proper screenings should be conducted on individuals who may be exposed to further risk if handling and use of the material result in excessive exposures.</p> <p>Not normally a hazard due to non-volatile nature of product</p> |
|----------------|--|

Continued...

## Zinc Filler

|                     |   |
|---------------------|---|
|                     | The inhalation of small particles of metal oxide results in sudden thirst, a sweet, metallic foul taste, throat irritation, cough, dry mucous membranes, tiredness and general unwellness. Headache, nausea and vomiting, fever or chills, restlessness, sweating, diarrhoea, excessive urination and prostration may also occur.<br>Inhalation of dusts, generated by the material during the course of normal handling, may be damaging to the health of the individual.  |
| <b>Ingestion</b>    | The material has <b>NOT</b> been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence.  |
| <b>Skin Contact</b> | Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.<br>Skin contact with the material may be harmful; systemic effects may result following absorption.<br>There is some evidence to suggest that the material may cause mild but significant inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering. |
| <b>Eye</b>          | Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may cause transient discomfort characterised by tearing or conjunctival redness (as with windburn). Slight abrasive damage may also result.<br>Contact with the eye by metal dusts may cause mechanical abrasion or foreign body penetration of the eyeball.   |
| <b>Chronic</b>      | Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.<br>There is sufficient evidence to suggest that this material directly causes cancer in humans.   |

|                    |   |  |
|--------------------|---|--|
| <b>Zinc Filler</b> | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                    | Not Available   | Not Available  |
| <b>zinc powder</b> | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                    | Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>   | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|                    |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
| <b>zinc oxide</b>  | <b>TOXICITY</b>   | <b>IRRITATION</b>  |
|                    | Oral (mouse) LD50: 7950 mg/kg <sup>[2]</sup>  | Eye (rabbit) : 500 mg/24 h - mild                                |
|                    | Oral (rat) LD50: >5000 mg/kg <sup>[1]</sup>   | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|                    | Oral (rat) LD50: >8437 mg/kg <sup>[2]</sup>   | Skin (rabbit) : 500 mg/24 h - mild                               |
|                    |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
| <b>Legend:</b>     | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |  |

|                    |  |
|--------------------|--|
| <b>ZINC POWDER</b> | Inhalation (human) TCLo: 124 mg/m <sup>3</sup> /50min. Skin (human):0.3mg/3DaysInt. mild   |
| <b>ZINC OXIDE</b>  | The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✗ | <b>Carcinogenicity</b>          | ✗ |
| <b>Skin Irritation/Corrosion</b>         | ✗ | <b>Reproductivity</b>           | ✗ |
| <b>Serious Eye Damage/Irritation</b>     | ✗ | <b>STOT - Single Exposure</b>   | ✗ |
| <b>Respiratory or Skin sensitisation</b> | ✗ | <b>STOT - Repeated Exposure</b> | ✗ |
| <b>Mutagenicity</b>                      | ✗ | <b>Aspiration Hazard</b>        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✔ – Data available to make classification

## SECTION 12 Ecological information

## Toxicity

|                    |                 |                           |                               |                     |               |
|--------------------|-----------------|---------------------------|-------------------------------|---------------------|---------------|
| <b>Zinc Filler</b> | <b>Endpoint</b> | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>        | <b>Source</b> |
|                    | Not Available   | Not Available             | Not Available                 | Not Available       | Not Available |
| <b>zinc powder</b> | <b>Endpoint</b> | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>        | <b>Source</b> |
|                    | EC10(ECx)       | 168h                      | Algae or other aquatic plants | 0.0025mg/l          | 2             |
|                    | EC50            | 96h                       | Algae or other aquatic plants | 0.042mg/l           | 2             |
|                    | EC50            | 72h                       | Algae or other aquatic plants | 0.005mg/l           | 4             |
|                    | LC50            | 96h                       | Fish                          | 0.01068-0.01413mg/l | 4             |
|                    | EC50            | 48h                       | Crustacea                     | 0.06-0.08mg/l       | 4             |

Continued...

## Zinc Filler

| zinc oxide | Endpoint  | Test Duration (hr) | Species                       | Value           | Source |
|------------|-----------|--------------------|-------------------------------|-----------------|--------|
|            | BCF       | 1344h              | Fish                          | 19-110          | 7      |
|            | LC50      | 96h                | Fish                          | 0.112mg/l       | 2      |
|            | EC50      | 72h                | Algae or other aquatic plants | 0.036-0.049mg/l | 4      |
|            | EC50      | 48h                | Crustacea                     | 0.105mg/l       | 2      |
|            | EC10(ECx) | 168h               | Algae or other aquatic plants | 0.0025mg/l      | 2      |
|            | EC50      | 96h                | Algae or other aquatic plants | 0.3mg/l         | 2      |

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

**DO NOT discharge into sewer or waterways.**

## Persistence and degradability

| Ingredient | Persistence: Water/Soil               | Persistence: Air                      |
|------------|---------------------------------------|---------------------------------------|
|            | No Data available for all ingredients | No Data available for all ingredients |

## Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------|-----------------|
| zinc oxide | LOW (BCF = 217) |

## Mobility in soil

| Ingredient | Mobility                              |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

## SECTION 13 Disposal considerations

## Waste treatment methods

|                              |   |
|------------------------------|---|
| Product / Packaging disposal | <ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. In most instances the supplier of the material should be consulted.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material)</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul> |
|------------------------------|---|

## SECTION 14 Transport information

## Labels Required



## Zinc Filler

|                         |   |
|-------------------------|---|
| <b>Marine Pollutant</b> |  |
| <b>HAZCHEM</b>          | 2Z  |

## Land transport (ADG)

|                                     |   |                      |
|-------------------------------------|---|----------------------|
| <b>UN number or ID number</b>       | 3077  |                      |
| <b>UN proper shipping name</b>      | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains zinc powder) |                      |
| <b>Transport hazard class(es)</b>   | Class   | 9                    |
|                                     | Subrisk   | Not Applicable       |
| <b>Packing group</b>                | III   |                      |
| <b>Environmental hazard</b>         | Environmentally hazardous   |                      |
| <b>Special precautions for user</b> | Special provisions  | 274 331 335 375 AU01 |
|                                     | Limited quantity  | 5 kg                 |

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in;

(a) packagings;

(b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L).

- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

## Air transport (ICAO-IATA / DGR)

|                                     |   |                         |
|-------------------------------------|---|-------------------------|
| <b>UN number</b>                    | 3077  |                         |
| <b>UN proper shipping name</b>      | Environmentally hazardous substance, solid, n.o.s. (contains zinc powder) |                         |
| <b>Transport hazard class(es)</b>   | ICAO/IATA Class   | 9                       |
|                                     | ICAO / IATA Subrisk   | Not Applicable          |
|                                     | ERG Code  | 9L                      |
| <b>Packing group</b>                | III   |                         |
| <b>Environmental hazard</b>         | Environmentally hazardous   |                         |
| <b>Special precautions for user</b> | Special provisions  | A97 A158 A179 A197 A215 |
|                                     | Cargo Only Packing Instructions   | 956                     |
|                                     | Cargo Only Maximum Qty / Pack   | 400 kg                  |
|                                     | Passenger and Cargo Packing Instructions                                  | 956                     |
|                                     | Passenger and Cargo Maximum Qty / Pack                                    | 400 kg                  |
|                                     | Passenger and Cargo Limited Quantity Packing Instructions                 | Y956                    |
|                                     | Passenger and Cargo Limited Maximum Qty / Pack                            | 30 kg G                 |

## Sea transport (IMDG-Code / GGVSee)

|                                     |   |                     |
|-------------------------------------|---|---------------------|
| <b>UN number</b>                    | 3077  |                     |
| <b>UN proper shipping name</b>      | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (contains zinc powder) |                     |
| <b>Transport hazard class(es)</b>   | IMDG Class  | 9                   |
|                                     | IMDG Subrisk  | Not Applicable      |
| <b>Packing group</b>                | III   |                     |
| <b>Environmental hazard</b>         | Marine Pollutant  |                     |
| <b>Special precautions for user</b> | EMS Number  | F-A, S-F            |
|                                     | Special provisions  | 274 335 966 967 969 |
|                                     | Limited Quantities  | 5 kg                |

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

| Product name | Group         |
|--------------|---------------|
| zinc powder  | Not Available |
| zinc oxide   | Not Available |

## Transport in bulk in accordance with the IGC Code

Continued...

## Zinc Filler

| Product name | Ship Type     |
|--------------|---------------|
| zinc powder  | Not Available |
| zinc oxide   | Not Available |

## SECTION 15 Regulatory information

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## zinc powder is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australian Inventory of Industrial Chemicals (AIIC)

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

## zinc oxide is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)  
International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

## National Inventory Status

| National Inventory                              | Status  |
|---|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes   |
| Canada - DSL                                    | Yes   |
| Canada - NDSL                                   | No (zinc powder)  |
| China - IECSC                                   | Yes   |
| Europe - EINEC / ELINCS / NLP                   | Yes   |
| Japan - ENCS                                    | No (zinc powder)  |
| Korea - KECI                                    | Yes   |
| New Zealand - NZIoC                             | Yes   |
| Philippines - PICCS                             | Yes   |
| USA - TSCA                                      | Yes   |
| Taiwan - TCSI                                   | Yes   |
| Mexico - INSQ                                   | Yes   |
| Vietnam - NCI                                   | Yes   |
| Russia - FBEPH                                  | Yes   |
| <b>Legend:</b>                                  | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

## SECTION 16 Other information

|               |            |
|---------------|------------|
| Revision Date | 22/02/2023 |
| Initial Date  | 29/08/2017 |

## SDS Version Summary

| Version | Date of Update | Sections Updated  |
|---------|----------------|---|
| 5.11    | 22/02/2023     | Toxicological information - Chronic Health, Ecological Information - Environmental, Exposure controls / personal protection - Exposure Standard, Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire fighting), Composition / information on ingredients - Ingredients, Physical and chemical properties - Physical Properties, Handling and storage - Storage (storage incompatibility) |

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
PC—STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit.  
IDLH: Immediately Dangerous to Life or Health Concentrations  
ES: Exposure Standard  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index

---

**Zinc Filler**

---

AIIC: Australian Inventory of Industrial Chemicals  
DSL: Domestic Substances List  
NDSL: Non-Domestic Substances List  
IECSC: Inventory of Existing Chemical Substance in China  
EINECS: European Inventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
NLP: No-Longer Polymers  
ENCS: Existing and New Chemical Substances Inventory  
KECI: Korea Existing Chemicals Inventory  
NZIoC: New Zealand Inventory of Chemicals  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
TSCA: Toxic Substances Control Act  
TCSI: Taiwan Chemical Substance Inventory  
INSQ: Inventario Nacional de Sustancias Químicas  
NCI: National Chemical Inventory  
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.