



Highway Alkyd Road Marking Paint

Rapid Dry

Data Sheet

FEATURES

- Approved for Transit New Zealand M7 (2009) Non-reflectorised A rating @ 180 microns dft
- Fast drying and excellent adhesion to aged road marking paint.
- Excellent resistance to bleeding of bitumen.
- NOT recommended for damp or wet surfaces. Ensure temperature is over 10° C.
- For line marking on all common roading surfaces.
- For Roads, Runways and Carparks etc.
- On unusual or non-standard surfaces the product should be trialled prior to use.

RECOMMENDED USES

A high performance fast-dry solventborne line-marking paint, possessing excellent drying and good wear resistance properties.

Ideal for use in company car parks, as hazard markings, and other uses / locations where traffic / pedestrian directions are needed.

SPECIFICATION DATA

Coating Type:	Alkyd
Colour:	White & Yellow
Packaging:	NZ: 4 litres (20 litre on special order)
Mix Ratio:	N/A
Gloss:	Matt
Thinner:	Petrol, toluene or Altex Thinner #10
Storage:	Store under cool, dry conditions

Density:	1.48 kg / litre
Volume Solids:	Yellow: 55% ±2%
	White: 60% ±2%

Theoretical Coverage Rate:

Yellow:	3.0 metres ² per litre at 180 microns dry
White:	3.3 metres ² per litre at 180 microns dry

Recommended Film Thickness Per Coat:

Yellow:	327 microns wet to obtain 180 microns dry
White:	300 microns wet to obtain 180 microns dry

Application: Spray, (brush or roll for small areas only)

Dry Times (180 µm DFT / 50% R.H. / 25°C):

No pick-up time:	7 – 11 minutes
------------------	----------------

SURFACE PREPARATION

Surfaces must be clean, dry, free from oil, grease, lichen, etc before application.

Can be applied to bare, unprimed or unsealed surfaces.

DIRECTIONS FOR USE

Airless Spray: Thinning is normally not required.

Stir thoroughly before use.

Brush or roller application is not normally recommended due to speed of drying.

For ease of application the product can be thinned up to 5% (v/v) with petrol or toluene when spraying. For small areas, Altex Thinner #10 will assist in brush / roller application.

PRECAUTIONS

For industrial use only. Read and follow all the caution statements on this Product Data Sheet, the product label and the Safety Data Sheet (SDS) for health and safety information prior to use.

Highway Alkyd Road Marking Paint is flammable. Keep away from heat, sparks and open flame. Use with adequate ventilation. May cause eye and skin irritation. Do not breathe vapour or spray. Wear suitable protective clothing such as gloves and eye and face protection.

WWW.ALTEXCOATINGS.COM

Head Office New Zealand Altex Coatings Ltd 91-111 Oropi Road Greerton, Tauranga 3112 Ph : +64 7 541 1221 Fax : +64 7 541 1310	Head Office Australia Resene Paints (Aust) Ltd Industrial & Marine Division 7 Production Avenue, Molendinar Queensland 4214 Ph : +61 7 5512 600 Fax : +61 7 5512 697	DISCLAIMER The information in this datasheet is provided as a guide only and is provided without warranty, implied or otherwise. It is your responsibility to determine the suitability of any information or product for the use contemplated. Conditions of use, application and the substrate are beyond our control so no liability whatsoever (whether as to coverage, performance, injury or otherwise) is accepted for the information contained herein. Data sheets may change from time to time and it is your responsibility to ensure you have the latest product datasheet and material safety data sheet from your supplier. Check the data sheet date with the listings at www.altexcoatings.com Altex Terms and Conditions of Trade, available at www.altexcoatings.com , apply in respect of all coating products and materials supplied, including samples.
--	---	--