

THINNING SOLVENT

Altex Thinning Solvent #45

DESCRIPTION

Altex Thinning Solvent #45 is a thinner to aid levelling and flow properties for select Carboline, Altex Yacht & Boat Paint single pack coatings and other coatings as recommended/specified by Altex Coatings.

DIRECTIONS FOR USE

Refer to the parent Product Data Sheet for further instructions.

TECHNICAL INFORMATION

Colour:	Clear	Storage:	Store under cool, dry conditions
Flash Point (setaflash):	31°C	Shelf Life:	60 months at 24°C
VOC:	810 g/L	When kept at recommended storage conditions and in original unopened containers. For products/components exceeding the stated shelf life, contact Technical Services for further advice.	
Packaging:	1 and 4 Litres		
NZ Only:	20 Litres		

PRECAUTIONS

For DIY & Professional Use: Read and follow all the caution statements on the current Product Data Sheet, the product label, and the Safety Data Sheet (SDS) for health and safety information prior to use. Refer also to the Hazardous Substances & New Organisms (HSNO) information in the Altex Yacht & Boat "General Safety Information" leaflet.

This product is flammable. Keep away from heat, sparks, and open flame. Use with adequate ventilation. May cause eye and skin irritation. Do not breathe vapour or spray. Wear suitable protective clothing such as gloves and eye and face protection.

It is very important for the safety of the applicator and the proper performance of this product that good ventilation be provided to all portions of the enclosed area. It is equally important to bring into the enclosed area dry fresh air to remove all solvent vapours. Since solvent vapours are heavier than air, ventilation ducts should reach to the lowest portions of the enclosed areas as well as into any structural pockets. Ventilation should be provided throughout the cure period to ensure all the solvents are removed from the coating.

WWW.ALTEXCOATINGS.COM

Head Office New Zealand
Altex Coatings Ltd
 91-111 Oropi Road
 Greerton, Tauranga 3112
 Ph: +64 7 541 1221
 Fax: +64 7 541 1310

Head Office Australia
Resene Paints (Aust) Ltd
Industrial & Marine Division
 7 Production Avenue, Molendinar
 Queensland 4214
 Ph: +61 7 5512 6600
 Fax: +61 7 5512 6697

DISCLAIMER

The information in this datasheet is provided as a guide only and is provided without warranty, implied or otherwise. It is your responsibility to determine the suitability of any information or product for the use contemplated. Conditions of use, application and the substrate are beyond our control so no liability whatsoever (whether as to coverage, performance, injury or otherwise) is accepted for the information contained herein.
 Data sheets may change from time to time and it is your responsibility to ensure you have the latest product datasheet and material safety data sheet from your supplier. Check the data sheet date with the listings at www.altexcoatings.com
 Altex Terms and Conditions of Trade, available at www.altexcoatings.com, apply in respect of all coating products and materials supplied, including samples.